

Alphanumeric pager W 09 N

[w09n]



If you are looking for a new alphanumeric pager, W09N would be one of your best options. W09N is a great brand new alphanumeric pager. With a large LED screen, it can display 4-8 lines of text, and memory capacity up to 3000 characters. It has out-of-range and low battery alert functions. And repeater message, unread message indication? Yes. The working frequency for this pager beeper is 137-930 MHz, supporting POCSAG or Flex (POCSAG and Flex). It is powered by a AAA battery, easily for you to replace the new one. Language support: Chinese, English, Germany, Korea, Turkey, Spanish, Farsi, French, Polish, etc... You may want to do you have the numeric pager? Recently, the cost for producing alpha pager and numeric pager is very close. Recently, we only keep manufacturing alpha pager. Why not have an alphanumeric pager which can receive both numeric and text at the same time? Motorola discontinued offering pager in 2000. So almost all Motorola pager you see in the market now are used or repaired ones. If you want to replace or add a new one for your system, W09N would be your good option. Alpha pager W09N is a user-friendly POCSAG pager. With a large screen, it can support 4 or 8-line display. Produced by high-quality plastic, it is a really durable device.

Specification

- Hand and PC programmable. USB ID programmer.
- PLL or crystal, 137-930 MHz, POCSAG or Flex
- Alert mode: Sound, vibrate, LED, Silent.
- 4 or 8-line English display, 3 zoom mode (English).
- Language support: Chinese, English, Germany, Korea, Turkey, Farsi, French, etc.
- Out-of-range, low battery, repeat message, unread message indicator.
- Menu selectable, User choice special functions for themselves.
- Second watch function

Technical parameters (POCSAG)

Frequency Range: 138-930 MHz
Cap Codes: 8
Receiver Type: Synthesized or Crystal
Baud Rate: 512, 1200, 2400 bps
Paging Sensitivity: -110 dB @ 512 bps
-108 dB @ 1200 bps
-106 dB @ 2400 bps
Channel Spacing: 25 KHz or 12.5 KHz
Frequency Deviation: +/- 4.5 KHz
Frequency Stability: +/- 10 PPM
Selectivity: > 55 dB
Image Rejection: > 52 dB
Spurious Rejection: > 55 dB
Intermodulation: > 50 dB
Alert Tone Loudness: 75 dB+ @ 12 inch
Display: 16 characters / line, 22 characters max
Memory Capacity: up to 3000 characters
Messages: 19 max
Weight: 68 g with battery
Dimensions: 76 x 53 x 18 mm
Battery Type: Single AAA
Low Battery Alert Level: 1.1 V
Operating Temperature: -10 to 50 C

Compatible Equipment

- Call button W12CB
- Alpha transmitter W11tk