

Repeater W 09 TR

[w09tr]



Sometimes, the region such as hospital, mall, construction site have building, tree to block the signal. Just connect the transmitter with power adapter and fix it in a suitable place. Then it work as a signal booster. It is so simple to booster the range of communication.

The coverage of service pager transmitter W09TR can up to 4km (diameter) with the repeater. If you want to build a wireless communication region within this rang, look no further.

The frequency of this service pager transmitter is 402-470Mhz. Using our paging software or yours (as it is a flexibility system) , you can send the text message to the alpha pager simply.

The package include:

- transmitter
- Antenna
- 7.5V or 12VDC adapter
- Data line.

Specification

Software Supported. You can use our software or yours, we have simple interface to use.

Flexible to fit any system

7-20VDC power support.

USB or 232 port supported.

TX Power 2W Max.

Can be using as a encoder to fit other transmitter

Repeater function

Technical parameters

Frequency range TX: 402-470 MHz

Frequency range RX: 402-470 MHz

Modulation Type: FSK

Channel Spacing: 12.5/25KHZ

Output Power: 2W max

Receiver sensitivity: -103DB

Harmonic Radiation: less - 25dBm

Frequency Stability: 5PPM at -10°C~60°C

Output Connect: BNC

Current Consumption Standby: 40mA;

Receive: 40mA;

Transmit: < 1A

Dimensions (no ANT): 110*62*22 mm

Weight (no ANT): 230g

Operating Temperature: -100 to 500 C

Compatible Equipment

- Alpha message transmitter W11tk

- Transmitter W11tk can transmit both number and text message. You can also program the text information by computer.