

POCSAG transmitter W 11 TK

[w11tk]



Wireless paging system transmitter w11tk is an idea pager transmitter.

It can send number and text message to alpha pager, coaster pager.

By the text area, you can simply transmitter signal to the pager by the related number. You can also send text message to the pager by keypad.

W11tk can also work with PC

Connect PC with data line. You can easily send numeric or alpha message to pager by paging software.

Benefit

Reduce guest anxiety

Run a smoother operation

Deliver orders at the proper temperature

Reduce Noise Pollution

Send text message easily

Specification

PLL or crystal, 402-470Mhz, POCSAG

Multi-language support

Alpha text input

PC setting and paging

1999 No. system

Technical parameters

Frequency range TX: 402-470 MHz

Modulation Type: FSK

Channel Spacing: 12.5/25KHZ

Output Power: 0.5-1W

Receiver sensitivity: -105DB

Harmonic Radiation: less - 25dBm

Frequency Stability: 5PPM at -10°C~60°C

Output Connect: BNC

Current Consumption Standby: 50mA; Transmit:<1A

Dimensions (no ANT): 167*83*40 mm

Weight (no ANT): 350g

Operating Temperature: -100 to 500 C

Compatible Equipment

Coaster pager w11ct

w11ct can work as a guest paging for restaurant, hospital. And w11ct can also display the text message sending from W11tk. It is also a valuable equipment for other service industries.